



**NeoGLS**  
Intelligent Transport

**OBU**  
(On Board Unit)

## CPU

---

NXP i.MX6 – ARM A9 4 x 1Ghz

## RAM

---

2 GB

## STORAGE

---

8 GB +  $\mu$ SD

## OPERATING SYSTEM

---

Linux Debian 9

## GNSS

---

GPS

Used for clock synchronization



## CONNECTIVITY

---

Ethernet 100Mbps full duplex

2x ITS G5

RS232

CAN

4 isolated digital outputs

4 digital inputs

3 analog inputs (continuous measurement 0-30v)

WiFi, Bluetooth

3G/4G, replaceable standard SIM card

External USB port

$\mu$ SD reader

*All radio connectors are in FAKRA format*

## REMOTE ACCESS

---

SSH v2 (root password provided)

Specific API, JSON for the LDM

SNMP

OpenVPN

SMS API

## ALIMENTATION

---

8-36v continued

Battery connector + contact to allow clean and deferred shutdown

## INTEGRATED SOFTWARE

---

ITS stack supporting

- ETSI Geonet

- CAM, DENM, SPAT, MAP, IVI and POI standards

- TS 103-097 security standard assisted by integrated hardware security module

- ETSI uppertester

Internal LDM with easy to use json API

*On demand software including MQTT and AMQP connectivity*

Site Montesquieu  
2 Allée Isaac Newton  
33650 Martillac - France

+33 5 57 96 11 66  
contact@neogls.com  
www.neogls.com